

## MINI COLD ROOMS

### QUICK-BOX



#### GENERAL FEATURES

The mini cold rooms are manufactured with closed-cell polyurethane foam panels with a density of 42 kg/m<sup>3</sup>, covered by white galvanised non-toxic plastic-coated sheet

The panels assembly is of camlock type with metal "eccentric" hook

Wall thickness is 70 mm, 60 mm for floor and 80 mm for ceiling

The exterior height is 2060 mm, the internal height is 1920 mm

Interior floor covering is:

- **standard**, in grey slip-proof galvanised plastic coated sheet

- **optional** (with additional price), in AISI 304 18/10 rusticated stainless steel R12

Interior ceiling covering is in white galvanised plastic-coated sheet

Exterior floor and ceiling covering is in galvanised sheet with plastic-zinc sheet perimeter moulding

All the mini cold rooms have floors with rounded interior corners and meet with strictest public-health standards

They are directly moulded in the sheet, without any visible seams

The door is hinged on the right with safety handle for opening from inside the cold room and the handle is complete with keylock  
For left hinged doors there is no added cost but need to be specified at order

The doors are equipped with an anti-condensate heated resistance on the door moulding

#### STANDARD PACKAGE

The cold room package is composed of the cold room and the monoblocks which can be straddled or ceiling ones  
Both types can be either in the TN (-2/+8 °C) or BT (-20/-15 °C) versions

The monoblocks are provided with a digital thermostat with visual and audible alarms automatically activated in case of need

The cold rooms are also equipped with internal light and a door microswitch which stops the fans and turns on the light at door opening


It is possible to order the cold room without holes, if needed

The mini cold rooms with TN temperatures are in 'T' class (43 °C)

The mini cold rooms with BT temperatures are in 'ST' class (38 °C)

Shelving is optional and it is made in ALUPLAST a light-grey AL-polyethylene composed of 4 grids shelves with a bearing capacity of 150 kg each

high heat insulation capacity



heat transmission coefficient K



camlock system



rounded floor  
R = 14 mm



gasket



handle



hinge



straddle MNBL



ceiling MNBL














package

standard

## MINI COLD ROOMS RANGE

model	external dim. WxDxH mm	internal dim. WxDxH mm	width panels (W mm) - H=1900mm										internal vol. m <sup>3</sup>
			1	2	3	4	5	6	7	8	9	10	
1212	1200x1240x2060	1060x1100x1920	1200	400	700	1200	400	700	-	-	-	-	2,16
1214	1200x1440x2060	1060x1300x1920	1200	600	700	1200	600	700	-	-	-	-	2,56
1216	1200x1640x2060	1060x1500x1920	1200	800	700	1200	800	700	-	-	-	-	2,97
1218	1200x1840x2060	1060x1700x1920	1200	400	700	600	1200	600	400	700	-	-	3,38
1220	1200x2040x2060	1060x1900x1920	1200	600	700	600	1200	600	600	700	-	-	3,79
1222	1200x2240x2060	1060x2100x1920	1200	600	700	800	1200	800	600	700	-	-	4,19
1224	1200x2440x2060	1060x2300x1920	1200	800	700	800	1200	800	800	700	-	-	4,60
1226	1200x2640x2060	1060x2500x1920	1200	800	700	1000	1200	1000	800	700	-	-	5,01
1228	1200x2840x2060	1060x2700x1920	1200	1000	700	1000	1200	1000	1000	700	-	-	5,41
1412	1400x1240x2060	1260x1100x1920	1400	400	700	1400	400	700	-	-	-	-	2,56
1414	1400x1440x2060	1260x1300x1920	1400	600	700	1400	600	700	-	-	-	-	3,05
1416	1400x1640x2060	1260x1500x1920	1400	800	700	1400	800	700	-	-	-	-	3,53
1418	1400x1840x2060	1260x1700x1920	1400	400	700	600	1400	600	400	700	-	-	4,02
1420	1400x2040x2060	1260x1900x1920	1400	600	700	600	1400	600	600	700	-	-	4,50
1422	1400x2240x2060	1260x2100x1920	1400	600	700	800	1400	800	600	700	-	-	4,98
1424	1400x2440x2060	1260x2300x1920	1400	800	700	800	1400	800	800	700	-	-	5,47
1426	1400x2640x2060	1260x2500x1920	1400	800	700	1000	1400	1000	800	700	-	-	5,95
1428	1400x2840x2060	1260x2700x1920	1400	1000	700	1000	1400	1000	1000	700	-	-	6,44
1612	1600x1240x2060	1460x1100x1920	1600	400	700	1600	400	700	-	-	-	-	2,97
1614	1600x1440x2060	1460x1300x1920	1600	600	700	1600	600	700	-	-	-	-	3,53
1616	1600x1640x2060	1460x1500x1920	1600	800	700	1600	800	700	-	-	-	-	4,09
1618	1600x1840x2060	1460x1700x1920	1600	400	700	600	1600	600	400	700	-	-	4,65
1620	1600x2040x2060	1460x1900x1920	1600	600	700	600	1600	600	600	700	-	-	5,21
1622	1600x2240x2060	1460x2100x1920	1600	600	700	800	1600	800	600	700	-	-	5,77
1624	1600x2440x2060	1460x2300x1920	1600	800	700	800	1600	800	800	700	-	-	6,34
1626	1600x2640x2060	1460x2500x1920	1600	800	700	1000	1600	1000	800	700	-	-	6,90
1628	1600x2840x2060	1460x2700x1920	1600	1000	700	1000	1600	1000	1000	700	-	-	7,46
1814	1800x1440x2060	1660x1300x1920	1800	600	700	1800	600	700	-	-	-	-	4,02
1816	1800x1640x2060	1660x1500x1920	1800	800	700	1800	800	700	-	-	-	-	4,65
1818	1800x1840x2060	1660x1700x1920	1800	400	700	600	1800	600	400	700	-	-	5,29
1820	1800x2040x2060	1660x1900x1920	1800	600	700	600	1800	600	600	700	-	-	5,93
1822	1800x2240x2060	1660x2100x1920	1800	600	700	800	1800	800	600	700	-	-	6,57
1824	1800x2440x2060	1660x2300x1920	1800	800	700	800	1800	800	800	700	-	-	7,20
1826	1800x2640x2060	1660x2500x1920	1800	800	700	1000	1800	1000	800	700	-	-	7,84
1828	1800x2840x2060	1660x2700x1920	1800	1000	700	1000	1800	1000	1000	700	-	-	8,48
2016	2000x1640x2060	1860x1500x1920	1000	1000	800	700	-	1000	1000	-	800	700	5,21
2018	2000x1840x2060	1860x1700x1920	1000	1000	400	700	600	1000	1000	600	400	700	5,93
2020	2000x2040x2060	1860x1900x1920	1000	1000	600	700	600	1000	1000	600	600	700	6,64
2022	2000x2240x2060	1860x2100x1920	1000	1000	600	700	800	1000	1000	800	600	700	7,36
2024	2000x2440x2060	1860x2300x1920	1000	1000	800	700	800	1000	1000	800	800	700	8,07
2026	2000x2640x2060	1860x2500x1920	1000	1000	800	700	1000	1000	1000	1000	800	700	8,79
2028	2000x2840x2060	1860x2700x1920	1000	1000	1000	700	1000	1000	1000	1000	1000	700	9,50

## MINI COLD ROOMS PANELS



## MINI COLD ROOMS PACKAGING

model	width	depth	height	volume
	W mm	D mm	H mm	m <sup>3</sup>
1212	2050	650	2200	2,9
1214	2050	650	2200	2,9
1216	2050	650	2200	2,9
1218	2050	650	2200	2,9
1220	2050	650	2200	2,9
1222	2250	700	2200	3,5
1224	2450	700	2200	3,8
1226	2650	700	2200	4,1
1228	2850	700	2200	4,4
1412	2050	650	2200	2,9
1414	2050	650	2200	2,9
1416	2050	650	2200	2,9
1418	2050	650	2200	2,9
1420	2050	650	2200	2,9
1422	2250	700	2200	3,5
1424	2450	700	2200	3,8
1426	2650	700	2200	4,1
1428	2850	700	2200	4,4
1612	2050	650	2200	2,9
1614	2050	650	2200	2,9
1616	2050	650	2200	2,9
1618	2050	650	2200	2,9
1620	2050	650	2200	2,9
1622	2250	700	2200	3,5
1624	2450	700	2200	3,8
1626	2650	700	2200	4,1
1628	2850	700	2200	4,4
1814	2050	650	2200	2,9
1816	2050	650	2200	2,9
1818	2050	650	2200	2,9
1820	2050	650	2200	2,9
1822	2250	700	2200	3,5
1824	2450	700	2200	3,8
1826	2650	700	2200	4,1
1828	2850	700	2200	4,4
2016	2050	650	2200	2,9
2018	2050	650	2200	2,9
2020	2050	650	2200	2,9
2022	2250	700	2200	3,5
2024	2450	700	2200	3,8
2026	2650	700	2200	4,1
2028	2850	700	2200	4,4

## MONOBLOCKS PACKAGING

STRADDLE monoblocks						
	ANA1	ANA2	ANB1	ANB2	ANC1	ANC2
W mm	480	480	530	530	850	850
D mm	920	920	950	950	1030	1030
H mm	770	770	870	870	970	970
vol. m <sup>3</sup>	0,34	0,34	0,44	0,44	0,85	0,85

	ABA1	ABA2	ABB1	ABB2	ABC1	ABC2
W mm	480	480	530	530	850	850
D mm	920	920	950	950	1030	1030
H mm	770	770	870	870	970	970
vol. m <sup>3</sup>	0,34	0,34	0,44	0,44	0,85	0,85

CEILING monoblocks						
	SNA1	SNA2	SNB1	SNB2	SNC1	SNC2
W mm	615	615	665	665	865	865
D mm	900	900	930	930	1040	1040
H mm	650	650	700	700	835	835
vol. m <sup>3</sup>	0,36	0,36	0,43	0,43	0,75	0,75

	SBA1	SBA2	SBB1	SBB2	SBC1	SBC2
W mm	615	615	665	665	865	865
D mm	900	900	930	930	1040	1040
H mm	650	650	700	700	835	835
vol. m <sup>3</sup>	0,36	0,36	0,43	0,43	0,75	0,75