



KLONDIKE

friggitrice ad induzione
induction deep fryer




- Struttura totalmente in acciaio inox.
- Pratico rubinetto per scarico dell'olio.
- Veloce, semplice ed estremamente facile da pulire.
- Comandi touch a prova di liquidi.
- Temperatura settabile fino a 190°, (range di temperatura 60°-190°).
- Funzione timer, fino ad un massimo di 120 minuti.
- Pratico visore digitale della temperatura.
- Pratico richiamo controllo olio all'accensione.
- Protezione termica di sovrariscaldamento.
- Arresto automatico dopo 2 ore.



- *Stainless steel structure.*
- *Handy tap for oil removal.*
- *Quickly heating and extremely easy to clean.*
- *Splash-proof touch controls.*
- *Temperature regulation up to 190° (range is from 60° to 190°).*
- *Easy setting timer to 120 minutes.*
- *Extremely visible digital display.*
- *Buzzer alarm to remind oil level check.*
- *Oil overheat protection.*
- *Automatically shut down after 2 hours.*



Pratico cestello da maneggiare
Easy to handle basket



Griglia ferma residui opzionale
Optional grid stops residues



| | | | | | | | A | B | C | D | E | F | | | |
|--------------------|-------|-----|------|-------|----|---------------|-----|-----|-----|-----|-----|-----|------|-------------|------|
| | watt | ph | min. | °C | lt | mm | mm | mm | mm | mm | mm | mm | kg | mm | kg |
| Klondike 8R | 3.500 | 1ph | 120 | 0÷190 | 7 | 180x218 h.135 | 247 | 345 | 290 | 440 | 590 | 407 | 12.2 | 565x350x478 | 13.9 |